



**Product:** Chronos – HC307 Wembley – Type 2

**Category:** Contract Wallpaper

## 1. Description

---

Our contractual 20oz (Type 2) embossed vinyl substrate with poly/cotton backing.

## 2. Suitable uses

---

This product can be used in hospitality and leisure groups, commercial and corporate spaces, retail interiors, restaurants and private residences.

## 3. Technical specifications

---

- Product weight: 450 grams per m2
- Width: 1.37 meters
- Length: 27 meter roll of wallpaper
- Substrate type: Embossed vinyl substrate with poly/cotton backing.
- Pattern repeat: Random
- Hanging instruction: Reverse hang
- Color fastness to light 200 hours: Good
- Color fastness: Bs2782- pass
- Impact resistance: Pass
- Smoke developed: 15
- Washability: Wipe able with warm water only, no detergents
- Stain Resistance: 1-12 ASTM D-1308-1987 Federal Spot Test
- Tear strength: 12 x 12
- Physical properties: Ccc-w-408a, b, c, d and ASTM e84
- Fire rating: ASTM E 84 A – 12C/ EN13501 B-s1, d0
- Chemical resistance: Resistant to temporary staining of oils, fats, mild acids and alkalis
- Breaking strength: 40 x 30

## 4. Wall Surfaces

---

- Walls should be smooth and flat, preferably primed with an oil based primer for good adhesion. Please consult our Wall Preparation Guideline for more information.
- It is the responsibility of the client/ professional/ contractor/ painter to ensure that walls are prepared correctly for wallpaper application. Failure to do so may result in a breakdown of the wall surface (delaminate) and WCI Wallpapers Pty Ltd accept no liability as a result of incorrect wallpaper preparation. If unsure, please contact us for more information about how to prepare your walls for wallpaper.
- It can also be recommended to size the wall with adhesive to create another layer for the wallpaper to adhere to. This can sometimes be useful if you do not know what the wall was painted with and creates a barrier for the wallpaper to adhere to and may prevent the possibility of the wall surface breaking down.
- Walls should also be checked for moisture content. Using a moisture meter, measure the wall surface and it is recommended that wall coverings should not be installed if the moisture reading is more than 5%.

## 5. Additional Information

---

- Product is recommended for internal use only by qualified professionals.
- Please get in touch with us if you require any further information about the product. You can contact our sales team via email at [info@wallcoverings.co.za](mailto:info@wallcoverings.co.za).

# WEMBLEY

HC307-7072 – HC307-7089



SELLERS & JOSEPHSON  
WALLCOVERING



Collection: **CHRONOS**

Description: **High End Contract Vinyl Wallcovering / TYPE II  
Naturally inspired Web Weave Emboss**

Composition: **Embossed Vinyl substrate (Cotton/Poly) Backing**

Width: **+ - 54 inches / + - 137cm**

Weight: **20oz per Linear yard / 620 gr per Linear Meter**

Pattern Repeat: **Random Match**

Hanging: **Random Reverse**

Fire Certification: **ASTM E 84 A - 12C / EN13501 B-s1,d0**

Custom Tariff Code: **3918.10.6000**

